

SIGNATURE LINE®

# RESOLUTE®

UNLIMITED MOISTURE VAPOR BARRIER,  
HARD-SET, ELASTOMERIC ADHESIVE

## PRODUCT HIGHLIGHT

Chasing moisture can cost valuable time and money, but with **Resolute**, you can stop it in its tracks. Designed with safe, single-part, moisture-cured chemistry, Resolute is a faster, more installer friendly alternative to two-part epoxy systems. Resolute is engineered for heavy rolling loads and challenging environments, and its waterproof design forms an unlimited moisture vapor barrier that can also take the punishment introduced by topical liquids.



### WHY USE

EXTREMELY  
▶ LOW  
ODOR

- Unlimited moisture protection (see TDS)
- Cost savings potential
- No moisture or pH testing required
- No sub-slab moisture barrier required (see TDS)
- Topical liquid resistance (water, spills, etc.)
- Permanent, waterproof bond
- 1-step installation (no stirring/mixing)
- Self-healing, elastomeric membrane
- Excellent plasticizer migration resistance
- Faster construction timeline
- 6-hour cure (heat weld, wet mop, strip/finish)
- Rapid occupancy times
- Extreme heavy rolling loads
- Installs multiple flooring types
- Sound control (IIC, STC)
- Low VOC, extremely low odor

NOW FEATURING NO TESTING

**COST SAVINGS POTENTIAL**

**Skip Testing:** Can save \$0.15/ft<sup>2</sup> by not having to moisture or pH test

**Start Installing:** Save days or weeks by avoiding costly construction delays

**Save \$4-5/ft<sup>2</sup>** by not having to bead blast, skim coat, or use a 2-part epoxy system

Savings are based on an estimated national average and may vary based on location and job site.



**COVERAGE: 50-250 ft<sup>2</sup>/gal**  
**AVAILABLE IN: 2 and 4 gal**  
**SHELF LIFE: 1 year**

SCAN HERE FOR PRODUCT INFORMATION

RH NTR* 100%	pH NTR* 5-14	MVER NTR*	OPEN TIME 0 MIN	WORKING TIME 45 MIN	CURE TIME 6 HRS	LIGHT TRAFFIC 3 HRS	HEAVY TRAFFIC 4 HRS	ROLLING LOADS 8 HRS	ΔIIC 18 dB**
--------------	--------------	-----------	-----------------	---------------------	-----------------	---------------------	---------------------	---------------------	--------------

800.868.4583  
tayloradhesives.com

**TAYLOR**  
A Meridian Brand

\*NTR = No Testing Required  
\*\*ΔIIC rating based on 6" concrete slab overlaid with 3.2 mm LVP flooring