

SIGNATURE LINE®

# RIDGELINE®

UNLIMITED MOISTURE VAPOR BARRIER,  
ELASTOMERIC ADHESIVE



## PRODUCT HIGHLIGHT

RESIDENTIAL

MULTI-FAMILY

COMMERCIAL

As the peak performer in its industry, **Ridgeline** rises above by offering complete protection for your wood floors. Ridgeline forms an unlimited moisture vapor barrier, resists alkalinity, and greatly reduces impact and sound transmission. With no moisture-related testing required, Ridgeline saves you valuable time and money.



### WHY USE

- Unlimited moisture protection (porous slab)
- Cost savings potential
- No moisture or pH testing required
- Permanent, waterproof bond
- Solvent and isocyanate-free
- Non-staining and easy to clean
- 1-step installation (no stirring/mixing)
- High-strength, elastomeric membrane
- Rapid occupancy times
- Faster construction timeline
- Sound control (IIC, STC)
- Warranted over cutback residue (see TDS)
- Protects flooring from alkali attack
- Extremely low VOC, extremely low odor

EXTREMELY  
▶ LOW  
ODOR

NOW FEATURING NO TESTING

**COST SAVINGS POTENTIAL**

**Skip Testing:** Can save \$0.15/ft<sup>2</sup> by not having to moisture or pH test

**Start Installing:** Save days or weeks by avoiding costly construction delays

**Save \$4-5/ft<sup>2</sup>** by not having to bead blast, skim coat, or use a 2-part epoxy system

Savings are based on an estimated national average and may vary based on location and job site.



**COVERAGE: 20-70 ft<sup>2</sup>/gal**  
**AVAILABLE IN: 4 gal**  
**SHELF LIFE: 1 year**



SCAN HERE FOR PRODUCT INFORMATION

RH 100%
 PH NTR\* 5-14
 MVER NTR\*
 OPEN TIME 0 MIN
 WORKING TIME 45 MIN
 CURE TIME 12 HRS
 LIGHT TRAFFIC 6 HRS
 HEAVY TRAFFIC 6 HRS
 STC 62 dB\*\*
 IIC 68 dB\*\*

800.868.4583  
tayloradhesives.com

**TAYLOR**  
A Meridian Brand

\*NTR = No Testing Required  
\*\*Ratings based on 6" concrete slab with a suspended wallboard ceiling overlaid with 3/8" engineered hardwood flooring